

EXTERIOR SEALER

1 – DESCRIPTION

Exterior Sealer is an one part acrylic sealant.

2 – PROPERTIES

- Very easy application.
- Forms a water tight plastic elastic sealant after curing.
- Resistant to rain.
- Excellent adhesion to damp and absorbent substrates.
- Frost resistant during transport down to -5°C.
- Solvent free.
- UV resistant.

3 - APPLICATIONS

- For sealing cracks, seams and connection joints that have a maximum 7.5% joint movement.
- Assembly wood, PVC and aluminium joinery.
- Sealing of window and door frame to masonry.
- Not suitable for joints exposed to continuous water immersion or joints which are totally closed.

4- PACKAGING

| Product | Volume | Package |
|-----------------|--------|---------|
| Exterior Sealer | 310ml | 24 |

Colors: **White**
Clear
Spruce
Light Oak
Mid Oak
Mahogany
Dark Brown

5- STORAGE AND SHELF LIFE

36 months in unopened packing in a cool, dry, storage place at temperatures between +5°C and +25°C

6- SAFETY

Do not allow product to freeze. Keep out of reach of children.

All tests with elongation and tensile strength are made under the conditions of ASTM D 412 C.

7- TECHNICAL PROPERTIES

Specific gravity : 1,52±0,03 g/cm³

Tack free time : 20-30 min. (23⁰C, % 50 humidity)

Completely dry time : 2 mm/24 hour (23⁰C , %50 humidity)

Ph : 8-9

Volume shrinkage : 28%

Weight loss : 20%

Elongation : >400%

Modulus 100% elongation : ≥0,20Mpa

Max. Tensile strength : ≥0,30Mpa

Tensile strength : ≥ 0,10 Mpa